

# Technical data sheet

## UPster H 500

Type: M2

Execution for: Turkey

Hood type dishwashing machine

3-phase current: 3N PE 400V 50Hz

Fresh water line: Soft cold water 0-3 °dH



Sample illustration

### Technical data

<b>Rack capacity/h (theoretical)</b>	40 / 24 / 17 racks/h
<b>Programme cycle time</b>	90 / 150 / 210 s
<b>Rack dimension</b>	500 x 500 mm (540 x 500)
<b>Entry height</b>	440 mm
<b>Dimensions (W x Hmin x D)</b>	635 ( 687) x 1470 x 750 (850) mm (with hood rod)
<b>Electrical feeding cable</b>	3-phase current 3N PE 400V 50Hz* Total connected load: 10,6 kW max. rated current: 19,6 A
<b>Local fuse protection</b>	20 A
<b>Protection class of the machine</b>	IP X4
<b>Equipment</b>	Control system MIKE CPU1 Infrared interface for wireless communication Automatic program start Leakage detector Boiler safety device Drain pump AktivPlus wash water filter system Automatic self-cleaning when tank is drained Back wall cladding
<b>Fresh water line</b>	Air gap 'AA' in accordance with EN 1717 with booster pump
<b>Fresh water supply</b>	Minimum flow pressure 60 kPa / 0,6 bar in front of solenoid valve Maximum pressure: 500 kPa / 5,0 bar Max. supply water temperature 60 °C
<b>Flow rate</b>	5 l/min
<b>Final rinse water quantity</b>	2,6 liters/cycle
<b>Boiler</b>	Contents: 10,5 l Heater: 7,50 kW Temperature: 83 °C

# Technical data sheet

<b>Wash tank</b>	Filling: 22,0 l Heater: 2,00 kW Temperature: 60 °C
<b>Wash pump</b>	Performance: 0,75 kW
<b>Dosing of rinse aid</b>	Hose pump (24 V) with time control and suction lance
<b>Detergent dosage</b>	Hose pump (24 V) with time control and suction lance
<b>Material</b>	Cladding: 1.4301 Wash tank: 1.4301 Boiler: 1.4571
<b>Heat emission</b>	for 25 programme cycles/h total: 2,7 kW perceptible: 1,8 kW latent: 0,9 kW
<b>Ventilation flow rate</b>	680 m <sup>3</sup> /h
<b>Steam emission</b>	1,3 kg/h
<b>Emission sound pressure level at the workplace (LpA)</b>	67 dB
<b>Net / gross weight</b>	113,0 kg / 140,0 kg (standard packaging)
<b>Packaging dimensions (W x H x D)</b>	800 x 1700 x 1000 mm (standard packaging)

## \*Note:

Electrical equipment suitable for supply voltage:  
3N PE 400 V 50 HZ (3N PE 380-415 V 50 Hz)